

TECHNICAL DATA

New ShaftAlign™ Touch

Setting the benchmark for solving common alignment problems



ADAPTIVE ALIGNMENT

Adaptive Alignment is a combination of software and hardware evolutions, enabling maintenance and reliability teams to address the full variety of horizontal, angular, and vertical alignment challenges.

With Adaptive Alignment solutions, work is completed faster, results are superior, and team capabilities are better utilized compared to other market solutions.

The new ShaftAlign™ Touch applies powerful Adaptive Alignment features to exceed the capabilities of conventional tools and deliver greater speed, accuracy, and elimination of human errors.

Introducing the new ShaftAlign™ Touch


The new ShaftAlign™ Touch laser alignment system provides digital, cloud, and other advancements over the widely used dial indicator and feeler gauge of past decades.

ShaftAlign™ Touch masters virtually any alignment task on standard machines driven by rotating shafts. Its laser precision results improve on those of conventional measurement equipment. It also offers simple and quick setup, intuitive handling through a computer-based and guided user interface, and an insightful visualization of results on the bright-colored 3D rugged tablet-like display.

Due to its rugged SensAlign™ 3 sensor and reflector, this new laser alignment system can handle almost any standard machine alignment challenge. With its problem-solving Adaptive Alignment features, the ShaftAlign™ Touch offers an unbeatable price-performance ratio.

Key benefits at a glance

- High performance and precise results**
The new ShaftAlign™ Touch leverages single-laser technology to provide high-precision, high-performance alignment measurements.
- Quick setup and intuitive user interface**
Its quickly mounted setup and tablet-like, intuitive guided user interface make the ShaftAlign™ Touch more user-friendly than any of the conventional measurement methods.
- Share data via the cloud**
You can leverage its integrated WiFi cloud solution to easily transfer measurement data from the ShaftAlign™ Touch handheld device to the ARC 4.0 software.



ShaftAlign™ Touch is user-friendly and easy to transport.



Why precision alignment is so crucial:


- Decreased power consumption
- Longer machine lifecycle
- Less vibration leading to less wear
- Lower temperatures on bearing, coupling and lubrication
- Reduced costs for spare parts storing

How Active Situational Intelligence (ASI) supports you

Active Situational Intelligence (ASI) is the core of Adaptive Alignment. It offers a range of problem-solving features based on intelligent software. ASI is a groundbreaking problem-solving technology that helps the user avoid mistakes while working quickly to measure and align machines.

Underestimated: Thermal growth

ShaftAlign™ Touch features an integrated Thermal Growth Calculator. Industrial materials such as steel and alloy typically expand when heated up. Only a few degrees are enough to impact the machine's behavior when running compared to the usual cold condition when alignment measurements are taken. The ShaftAlign™ Touch Thermal Growth Calculator automatically factors the expected deviation into the measurement result.





Adaptive Alignment: Adapt to the situation

Measure over different types of couplings

ShaftAlign™ Touch provides a wide range of coupling types, making it easier for the user to receive an optimal measuring result without deviating from the specific tolerances. Choose the right coupling adapted to your onsite situation:

- short flex coupling
- spacer shaft
- single plane coupling
- uncoupled shafts
- further various default coupling formats



Adaptive Alignment: Adapt to the team

Intuitive user interface to benefits all types of users

Prüftechnik, the inventor and pioneer of laser shaft alignment, offers years of experience in designing systems to serve technicians in the field. The new ShaftAlign™ Touch offers a colored 3D user interface that is the key to executing alignment tasks quickly and easily without sacrificing accuracy.

Cloud-based transfer enables data sharing and trending

All Prüftechnik alignment systems now offer WiFi connectivity to remotely transfer data from and to the ARC 4.0 PC software, where one can store, share, evaluate, and trend all alignment data. Cloud-transfer capabilities enable entire maintenance teams to stay informed and alerted to potential issues that might interrupt production.



Adaptive Alignment: Adapt to the asset

The best results for use on standard machines

How ShaftAlign™ Touch improves on the performance of traditional alignment tools:

- Faster setup than any dial indicator
- Higher precision than any feeler gauge
- No sagging, even over large distances, due to having laser technology
- Quicker and easier to read results than through a manual matrix calculation
- Ability to operate the device independent from what may be occurring on the coupling/shaft surface

Want to learn more?

Contact us at PRUFTECHNIK.com



Shaft Alignment Tablet

General specifications		
CPU	Processor: Memory:	Octa-Core (8): 2.2 GHz (2) and 1.8 GHz (6) 4 GB LPDDR4X SDRAM/64 GB UFS Flash
Display	Technology: Resolution: Dimensions:	Corning® Gorilla® Glass 600 nits, color WXGA 1280x800 8 inch/20.3 cm
Power Supply:	Operating time: Battery: Charging:	Up to 11 hours 6100 mAh 3.87 V rechargeable Li-Ion Polymer; (23.61 Wh) USB-C
Connectivity	Wifi: Bluetooth: RFID:	IEEE 802.11 a/b/g/n/ac/d/h/i/r/k/v/w/mc/ax 2x2 MU-MIMO; Wi-Fi® certified; IPv4, IPv6 (Wi-Fi 6) Bluetooth v5.1 / 2.1+EDR Class 2 (Bluetooth LE) Integrated RFID with read and write capabilities Docking connector (charge and data) USB-C side port (tablet charging and data only)
Environmental protection	IP 65: Relative humidity	Dustproof and water jets resistant 5% to 95% non-condensing
Drop test		1.2 m (4 ft)
Temperature range	Operation: Storage:	-20°C to 50°C (-4°F to 122°F) -40°C to 70°C (-40°F to 158°F)
Dimensions		267 mm L x 171 mm H x 35 mm D 10 33/64" x 6 47/64" x 1 3/8"
Weight		930 g/2.1 lbs
Camera	Rear: Front:	Rear: Image capture: 13 MP auto-focus camera with user controllable LED flash 5MP
CE conformity		Refer to the CE compliance certificate in www.pruftechnik.com
Carrying case	Standard Dimensions Weight	595 x 355 x 115 mm (23 1/2" x 14" x 4 1/2")

Reflector (prism)

General specifications		
Type		90° roof prism
Accuracy (avg)		> 99%
Environmental protection		IP 67 (submersible, dustproof)
Temperature range	Operation: Storage:	-20°C to 60°C (-4°F to 140°F) -20°C to 80°C (-4°F to 176°F)
Dimensions		Approx. 100 x 41 x 35 mm (4" x 1 5/8" x 1 3/8")
Weight		Approx. 65 g (2.3 oz)

Fluke Corporation
 PO Box 9090, Everett, WA 98206 U.S.A.
 For more information call:
 In the U.S.A. 856-810-2700
 In Europe + 49 8999616 420
 In UK +44 1543 417763
 Email: fds-support@fluke.com
 Web access: fluke.com

©2025 Fluke Corporation. Specifications subject to change without notice. 03/2025 fr-250127-en

Modification of this document is not permitted without written permission from Fluke Corporation.

SensAlign™ 3 sensor

General specifications		
Measurement principle		Coaxial, reflected laser beam
LED indicators		1 LED for laser beam status and battery status 1 LED for Wireless communication
Power supply	Battery: Operating time: Charging time:	Lithium-Ion rechargeable battery 3.7 V / 5 Wh 10 hours (continuous use) Using charger – 2.5 h for up to 90% 3.5 h for up to 100% Using USB port – 3 h for up to 90% 4 h for up to 100%
Environmental protection	IP 65: Relative humidity:	Dustproof and water jets resistant, shockproof 10% to 90% (non-condensing)
Ambient light protection		Yes
Temperature range	Operation: Charging: Storage:	-10°C to 50°C (14°F to 122°F) 0°C to 40°C (32°F to 104°F) -20°C to 60°C (-4°F to 140°F)
Dimensions		Approx. 105 x 69 x 55 mm (4 9/64" x 2 23/32" x 2 11/64")
Weight		Approx. 210 g (7.4 oz) with dust cap
Detector	Measurement range: Resolution: Error (avg):	Unlimited, dynamically extendible 1 µm (0.04 mil) and angular 10 µRad < 2%
Inclinometer	Measurement range: Resolution: Inclinometer error:	0° to 360° 0.1° 0.3% full scale
Laser	Type: Wavelength: Safety class: Beam power: Beam divergence: Safety precautions:	Semiconductor laser diode 630 - 680 nm (red, visible) Class 2 according to IEC 60825-1:2014 The laser complies with 21 CFR 1040.10 and 1040.11 except for deviations pursuant to Laser Notice No. 50, dated June 24, 2007. < 1 mW < 0.3 mrad Do not look into laser beam
External interface		Wireless communication
Transmission distance		Up to 30 m (98 ft) direct line of sight
CE conformity		Refer to the CE compliance certificate in www.pruftechnik.com
Country radio certifications		Approvals granted for specific regions (refer to the provided 'Safety and general information' document)

